



















24V Flood light Units

Cable: 2 or 4 pin PVC and UV stabilised ca-

ble 1.5mm (various lengths)

Sizes: 10 watt, 15 watt, 18 watt, 30 watt, 54

watt, 86 watt (larger units available)

Protection: Rated at IP65 for permanent

outdoor

applications - Submergible available **Safety:** Low voltage DC FOR SAFETY **Longevity:** Long life diodes, permanent out-

door quality with warranty included

Flood Light Sizing

54WATT Flood Light: 225x 185x125 Two 500mm tails (1 male, 1 female) Power: 24 Volts Weight: 1.8KG

Outdoor quality: IP65

86WATT Flood Light: 226x 187x160

Two 500mm tails (1 male, 1 female) **Power:** 24 Volts **Weight:** 2.9KG

Outdoor quality: IP65

Features

For outstanding output increase the size of your wash lights.

24 volt output **Bold** Illumination with adjustable brightness

3-in-one RED, GREEN, BLUE diodes or Solid colour with memory function. Colour changing and functions available via remote. Strobes, fades, dimmable

Grey or black enclosure. Male / female

end-to-end connectors.

Flood LIGHTS OVERVIEW

24V Flood light Units

Cable: 2 or 4 pin PVC and UV stabilised cable

1.5mm (various lengths)

Sizes: 10 watt, 15 watt, 18 watt, 30 watt, 54 watt,

86 watt (larger units available)

Protection: Rated at IP65 for permanent outdoor

applications - Submergible available

Safety: Low voltage DC FOR SAFETY

Longevity: Long life diodes, permanent outdoor

quality with warranty included

Flood Light Sizing



54WATT Flood Light: 225x 185x125 Two 500mm tails (1 male, 1 female) Power: 24 Volts Weight: 1.8KG

Outdoor quality: IP65



86WATT Flood Light: 226x 187x160 Two 500mm tails (1 male, 1 female) Power: 24 Volts Weight: 2.9KG

:Connection Made

:Connection Secured

Outdoor quality: IP65

Features

For outstanding output increase the size of your wash lights.

24 volt output Bold Illumination with adjustable brightness

3-in-one RED, GREEN, BLUE diodes or Solid colour with memory function.

Colour changing and functions available via remote. Strobes, fades, dimmable

Grey or black enclosure. Male / female end-to-end connectors.

- A Extension Leads; Various sizing and custom available
- B -Colour controllers: radio frequency, infrared, WIFI
- application

C - Power supplies, sizes to match the

If required use extensions to take power from the power supply to the first flood light unit.

Place extensions between each flood light to spread the wash of light across the desired area.

Perfect for creative garden displays, marquees, highlighting features, bridal backdrops, stage productions and more

LIGHTING PACKAGES AVAILABLE



Accessories Available



Connectable - Designed for the event industry





Our lighting systems all share the same connectable principle. Using one power outlet, our wash lights big or small can be 'daisy-chained' along to create dynamic lighting arrangements.





DID YOU KNOW? You can connect our fairy Light & festoon lighting systems to the same power supply!!

How to connect a 24v system with a colour controller





COLOUR CONTROLLER OPTION



PRODUCT SPECIFICATION

Enclosure type power supply



POWER SUPPLY OPTIONS

SWITCH MODE POWER SUPPLY 350 WATT

AC-DC power supply

*Supply Voltage:100-120v/ 220~240VAC

*Total Power: 350W 12vDC 29.16A / 24vDC 14.58A

*Dimensions:220*115*50mm
*G.W:1KG *.Approval: CE ROHS

*IP55 enclosure with 2 or 4 24vdc female

outlets (30cm)

*AS/NZ 3 pin x 1.5 metre 240v AC input

(100 watt to 600 watt models available)

Application & notes

CUSTOM MADE POWER SUPPLIES SET IN AN IP55 ENCLOSURE WITH 2 OR 4 24 VOLT OUTLET TAILS. IDEAL FOR DRIVING LARGE FEATURE LOWVOLTAGE LIGHTING.

E.G. switch mode low voltage power supply



2 or 4 24vdc female outlets (30cm)



2 X female 45cm leads on 24vdc side



Low voltage power supply



POWER SUPPLY IP67 240~24VDC ~200watt

AC-DC power supply IP67

*Supply Voltage: 100-120/220-240VAC 50/60Hz

*Total Power:200W (12V 16.5A) (24V8.3A) *Dimensions:228x120x63mm *G.W:2.5KG

*.Approval: CE & RoHS

*240v AC input :1.5 metre lead with AS/NZ 3 pin

plug top

*24V outlet: 2 X female 45cm leads on 24vdc side

(40watt to 320 watt models available ex stock)

SUITABLE FOR INDOOR or EXTERNAL USE ROBUST CONSTRUCTION, RELIABLE SUPPLY CHOICE OF WATTAGE SIZE AVAILABLE ALL WITH 3 PIN STANDARD PLUG

Product Specification	WASH & FLOOD ACCESSORIES	Application & notes
	24 volt extension leads 2 and 4 pin options 2 & 4 stands inner encased in uv protected outer sheath male and female screw together connector able sections suitable for low voltage current only black flex only rated at ip44 for outdoor or indoor use	Use to extend span of lights or to bring power to light fitting from the power supply
Dec alight com as	24v 2 or 4 Pin Y Splitter 3 way connector connector length 300mm One male connector for lead cord inlet power 2 female for outlet power black pvc flex only for 24 volt range only IP44 rated	use splitters to split light units in dif- ferent directions or to create power belts
Decolight com au	24 v colour controller 288 Watt max out put in rgb mode 8 colour selection & 2 mode settings One male connector for lead cord inlet power 24v 1 female for outlet 24v power black or white PVC flex only for 24 volt range only IP20	Unit has memory so will always start at last setting that has been input. it is out recommendation to not exceed the rated output value 288watt
Wi Fi LED Controller	WIFI colour controller WIFI Unit for remote colour change of rgb lighting 29 modes and 288 watt output full colour	Allows colour change from cell phone application DECORATIVE LIGHTING COMPANY www.decolight.com.au